# ASSEMBLING & INSTALLATION INSTRUCTIONS PRODUCT# OXFORD SERIES OUTDOOR POST MOUNT LIGHT FIXTURE

#### WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

### ASSEMBLING THE FIXTURE (Fig.1).

- 1. Carefully unpack new fixture and lay all the parts on a clear surface. Take care not to lose any small parts necessary for installation.
- 2. Install the light bulbs(no included) in accordance with the fixture's specifications. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**
- 3. Raise the glass shade into the lamp body(C). Attach the cover(A) to the lamp body(C), lock it securely with the hex nut(B).
- 4. Attach the assembly lamp body onto the post(no included) and lock it securely with the screw.

## Wiring (Fig.2)

- 1. Connect the electrical wires as follows. Connect the black wire from the fixture to the black house (hot) wire. Connect the white wire from the fixture to the white (neutral) house wire. Make sure all wire nuts are secured. You may wrap the connections with electrical tape. If your outlet box has a ground wire (green or bare copper) connect fixture's ground wire to it. Otherwise attach the bare copper fixture wire to the
  - Otherwise attach the bare copper fixture wire to the green ground screw on the circular strap.
- 2. Tuck the wire connections neatly into the junction box.

Your installation is now complete. Return power to the junction box and test the fixture.

#### Fig.2 FIXTURE FIXTURE FIXTURE WIRES WIRES WIRES Black or White or Bare Smooth Ribbed Copper (Ground) HOUSE HOUSE WIRES WIRES WIRES **Black** White Green or (Hot) (Neutral) Bare Copper (Ground)



