

120V-277V LED Large Flood, 85W



Select Models

PROJECT: \_\_\_\_\_

TYPE: \_\_\_\_\_

ORDERING: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

### APPLICATIONS

Kichler's 120V-277V LED flood lighting fixtures are designed for outdoor lighting applications requiring uniform light sources, with long life, and little maintenance requirements.

### CONSTRUCTION

Die-cast aluminum construction with durable polyester powder coating. Vandal resistant hardware, reinforced knuckle design, a water draining front end with an integrated cowl.

### ELECTRICAL

ETL listed to UL and CSA Standards for 120V-277 VAC (50/60 Hz), and suitable for wet locations. Integrated surge protection (4kV) comes standard.

### OPTICS

Utilizes a two LED chip-on-board light source that provides for center-to-edge uniformity and enhances beam control. NEMA 7 x 6 wide flood. Three-step binning for tight color consistency.

### LISTINGS

ETL wet label listed to UL and CSA Standards. IP66 rated. FCC compliant.

### ORDERING MATRIX (Model # +Finish & CCT Codes) & LUMEN INFORMATION

The standard model is the Knuckle Mount Fixture. For Slip Fit or Trunnion, add SL or TR respectively.

Model #	Finish	CCT (30 / 40)	Mount	Wattage	CRI	Lumen	Lm/W	L70 (hrs)
16225	AZT or BKT	3000K	Knuckle	84.9	80 (+)	7529	89	60,000
*16225	AZT or BKT	4000K	Knuckle	84.6	80 (+)	8613	102	60,000

### ADDITIONAL MOUNTING OPTIONS



Slip-Fit Mount



Trunnion Mount

**Example:** 16225BKT40 is model 16225 in Textured Black, 4000K (to then change from knuckle to Slip Mount, add SL after 40)


Each model is available with a finish in BKT - Textured Black or AZT - Textured Architectural Bronze

\*DLC Qualified Products. For the most current listing, visit [www.designlights.org](http://www.designlights.org)

# C-Series LED

120V-277V LED Large Flood, 85W

## DIMENSIONS



## INCLUDED ACCESSORIES

Three (3) King Innovation Gel-Filled twist-on wire connectors

## ACCESSORIES

Ordered & shipped separately (for knuckle only)

<b>15645 AZT, BKT</b> - 6" Stem	Corrosion resistant
<b>15656 AZT, BKT</b> - 12" Stem	aluminum alloy with
<b>15657 AZT, BKT</b> - 18" Stem	baked thermoset
<b>15658 AZT, BKT</b> - 24" Stem	powder coating.


**15276 BKT** - Power Post: A Fast, One-Step Connector Made of Impact / Corrosion Resistant PVC 2.25" Inside Diameter to Accommodate Conduits of Different Sizes Accepts .50 NPSM Thread Designed For 120V-277V Line Voltage Landscape Lighting, Eliminating Need For Above or Below Ground Boxes. Built-in Stabilizer Removes Need For Concrete

**15601 AZT, BKT** - Cast Aluminum Surface Mounting Flange with Bronze or Black Finish, Neoprene Gasket For Watertight Seal

**15609 AZT, BKT** - Junction Box Mounting Bracket Corrosion Resistant Cast Aluminum Alloy with Baked Thermoset Bronze or Black Powder Coat Finish

## PHOTOMETRIC DIAGRAMS

16225 Large Flood



16225BKT30 shown (7300 Lumens)