

Assembly Instructions: 9808-BA3/LSF (Seaport)

IMPORTANT:

- ALL INSTALLATION WORK SHOULD BE DONE BY ACCREDITED PROFESSIONAL.
- SHUT OFF POWER SUPPLY AT FUSE OR CIRCUIT BREAKER!
- USE ONLY THE SPECIFIED BULBS. DO NOT EXCEED THE MAXIMUM WATTAGE!

For Customer Service, please contact the place of purchase.


PREPARING FOR INSTALLATION

Remove all of the contents from the carton. See the important notes above. Shut off the power at the circuit breaker and completely remove the old fixture from the wall or ceiling, including the old mounting strap.

Please Note: This fixture may be mounted on the wall or ceiling.

1. Mounting strap (A) may be attached to backplate (G). If the mounting strap is attached, remove screws (B) to detach. The mounting strap contains several pairs of threaded holes. Find the pair of holes that matches the spacing of the holes on the junction box and your fixture's backplate. Test backplate (G) on mounting strap (A) to ensure that the backplate will hang straight. Place the fixture aside. Gently pull the house wires from the junction box through the center of mounting strap (A).

2. Place mounting strap (A) over the junction box so that mounting screws (D) may be inserted. Secure mounting strap (A) to the junction box with mounting screws (D) and a screwdriver. Tighten the mounting screws (D) securely.



CONNECTING THE WIRES

3. Attach the fixture's wires to the power supply wires from the junction box. Connect black to black (or smooth); white to white (or ribbed); ground to ground (green or copper). Twist the ends of the wire pairs together, then twist on a wire connector. Make sure all twists are in the same direction. If there is no ground wire (green or copper) from the junction box, locate ground screw (E) on mounting strap (A) and wrap the fixture's ground wire around the green ground screw (E). Use a screwdriver to secure ground screw (E) onto the mounting bracket. Tuck all wires neatly into the junction box.

How to Identify the Fixture's Wires			
Hot	Neutral	Ground	
Smooth	Ribbed	Bare Metal, Green, or Green Inner Thread	
Black	White		
Black Inner Thread	White Inner Thread		

FINISHING THE INSTALLATION

4. Place the fixture's backplate (G) over mounting strap (A) so that the holes in mounting strap (A) line up with the holes in backplate (G). Use the provided screwdriver to thread screws (B) into backplate (G) until backplate (G) is snug against the wall or ceiling.

6. Install light bulbs (not provided) based on the fixture's specifications. Do not exceed the maximum wattage.

7. Slide metal cages (H) up to the bottom of caps (I). Secure the metal cages in place with decorative nuts (F).

Please note that you can move the light sources at joints (C) to adjust the direction of the light.

Your installation is complete. Turn on the power and test the fixture.

CLEANING TIPS

Treat the fixture gently! Regular cleaning will reduce the need for deep cleaning. For regular cleaning, turn off the light and wipe down the fixture with a clean lint-free cotton or microfiber cloth. Never spray cleaner directly onto the fixture.