Disc LED Ceiling and Wall

FM-30

WAC LIGHTING

Responsible Lighting®



Fixture Type:								
Catalog Number:								
Project:								
Location:								

PRODUCT DESCRIPTION

Multiple mid-powered LEDs illuminate the acrylic diffuser uniformly without socket shadows which are common in conventional flush mounts.

FEATURES

- Energy Star® rated
- · Wet Location Listed
- CEC Title 24 Compliant
- CSA listed
- ADA compliant
- Wall or Ceiling Mount
- Translucent acrylic diffuser
- Multiple LED array for uniform illumination
- 120VAC no driver needed
- Smooth and continuous ELV dimming
- 36,000 hour rated life
- 5 year warranty

SPECIFICATIONS

Construction: Steel with white acrylic diffuser

Input: 120VAC

ELV Dimming: 100% - 10% Electronic Low Voltage

Harmonic Distortion (THD): 16% for Input Current at 120VAC

Operating Temperature: -35°C (-31°F) to 50°C (122°F)

ORDERING NUMBER

		Watt	Mounting	Color Temp CI		CRI	LED Lumens	Delivered Lumens	Finish		
5%" I 1%"	FM-304	12.5W	Retrofit over a 4" recessed can or install over a 3" or 4" junction box	930	3000K	90	835	650	BN BZ WT	Brushed nickel Bronze White	
7%"	FM-306	15.5W	Retrofit over a 5" or 6" recessed can or install over a 4" junction box only	930 940	3000K 4000K	90 90	1010 1235	865 905	BN BZ WT	Brushed nickel Bronze White	
73%"	FM-306	15.5W	Install over a 3" or 4" junction box	930JB	3000K	90	1190	940	wT	White	

FM-30____-

Example: **FM-306-940-WT**

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760