

#### PRODUCT DETAILS:

- Wattage settings includes: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- Suitable for use in wet (outdoor direct rain or sprinkler) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards
- Photometrics based off engine photometrics.
- Incorporates CREE LEDs with application performance tested by CREE
- PVC constructed concrete pour kit and burial sleeve is supplied.
- Includes a dense foam cap to prevent concrete from entering
- LumaCore Series products carry a lifetime limited warranty
- Sophisticated and streamlined design, durable construction and timeless finish complement any architectural style

## VARIABLE OUTPUT LED 30K GRILL TOP WELL LIGHT

### 15705BZ-LMA30K

VARIABLE OUTPUT LED 3K GRILL TOP WELL LIGHT

The LumaCORE LED accent lighting system is an expertly engineered core that withstands the elements and provides the user with full control over wattage and color temperature.

DETAILS	
FINISH:	Bronze
MATERIAL:	Aluminum
GLASS:	Clear Lens

#### DIMENSIONS

DIMENSIONS	
WIDTH:	4.8"
HEIGHT:	4.8"
DEPTH:	4.8
WEIGHT:	3lb

LIGHT SOURCE	
LIGHT SOURCE:	Integrated LED
LED NAME:	30G4SE-12W
VOLTAGE:	12v
COLOR TEMP:	3000
CRI:	80
INCANDESCENT EQUIVALENCY:	1 x 60w, 45w, 35w, 25w
DIMMABLE:	No
TRANSFORMER REQUIRED:	Yes

MOUNTING	
LEAD WIRE:	1 X 36"

SHIPPING	
CARTON LENGTH:	7
CARTON WIDTH:	7
CARTON HEIGHT:	13.5
CARTON WEIGHT:	4.5

# HINKLEY