

# VALERA

Wall vertical mounted • Wet location listed



## Description:

Clean lines are up front and center for these modern LED outdoor sconces. Valera features a die-cast aluminum frame and matte white, acrylic diffuser. Energy efficient LED source offers 3000K color temperature and 90+CRI output. Title 24 compliant. Two-light 9w LED wall lantern in a Brushed Nickel finish.

## Specifications:

- Brushed Nickel (-09) (Plated)
- Aluminum construction
- Polycarbonate acrylic diffuser
- 120VA replaceable LED Module (part # 93054049) Modern LED outdoor sconce.
- Clean lines are central to design.
- Features a die-cast aluminum frame and matte white, acrylic diffuser.
- Meets California Title 24 high efficacy requirements for outdoor use only.
- Dimmable to 10% with many ELV dimmers
- 623 lumens 69.2 lumens/watt
- 3000K color temperature, 90+ CRI
- Dimmable to 10% brightness (See Dimming Notes)
- Chassis covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- Complies with "Americans with Disabilities Act" - ADA
- ENERGY STAR® qualified
- Meets California Title 24 high efficacy requirements for outdoor use only

## Performance:

Number of Modules	2
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	623/69.2 (LM-79) per module
CCT	3000 K
CRI	90+
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed
	ENERGY STAR® qualified
	Meets California Title 24 high efficacy requirements for outdoor use only

## P5806-0930K9

## Images:



## Dimensions:

Width: 5-5/8"  
Depth: 4"  
Height: 16"  
H/CTR: 8"

# VALERA

Wall vertical mounted • Wet location listed




## Photometrics:

P5806-0930K9

ELECTRICAL DATA	P5800-0930K9
Input Voltage	120 V
Input Frequency	60 Hz
Input Current	
Input Power	9
Power Factor	
THD	<20%
EMI Filtering	FCC Title 47, Part 15 Class B
Operating Temperature	-30 °C to 30 °C
Dimming	Yes*
Over-voltage, over-current, short-circuit protected	
*See Dimming Notes for more information	

**P5800-0930K9**  
 LED Light Engine: 3000 K 90+ CRI  
 System Wattage: 9  
 Fixture delivered lumens: 623  
 Fixture Efficacy: 69.2  
 Spacing Criteria:



## ZONAL LUMEN SUMMARY