

JOB NAME _____

CONTACT _____

ORDERING CODE _____

LM-79

SURFACE MOUNT SQUARE Cube Downlight



DESCRIPTION

The Surface Mount Square has a 3-1/2" aperture. 14°, 24° and 34° reflector options. It is offered in white or black finish aluminum housing. 0-10V dimming is standard. The Surface Mount Square carries a 5 year LIMITED FIXTURE WARRANTY.

HOUSING

Machined aluminum housing in white or Black finish. Standard clear lens provided.

MOUNTING

- Easy mounting system over a 3-1/2" to 4" recessed octagonal junction box for S, RP, and RPS mounting options.
- RP mounting option can be mounted on ≤ 45° sloped ceiling (fixture is a self-contained operating unit, wiring through stem by others). Consult factory for custom pendant lengths.
- RPS mounting option is a fixed stem length pendant with slim junction box cover. Select stem lengths from ordering code.
- QCRP mounting option requires a 4" surface mount octagonal junction box. For more details, refer to Conduit Mount spec sheet.

LISTINGS

- ETLus Listed to UL1598 (suitable for dry and damp locations)
- cETL Listed to CSA C22.2 #250.0

LED INFO

- LUXEON 1203: Duv +/- 0.0015, Lumen Maintenance: L₇₀ > 50,000 hrs

ORDERING CODE	
SERIES	138230
APERTURE	3.5 3.5"
DELIVERED LUMENS	11LM 970 lm 15LM 1250 lm
CCT	30K 3000K
CRI	90 90 CRI
REFLECTOR	SA14 14° specular SA24 24° specular SA34 34° specular
VOLTAGE	UNV 120V-277V
DIMMING	DIM10 0-10V dimming to 1%
FINISH	BK black WH white
MOUNTING OPTIONS	S surface mount RP rigid pendant RPS ¹ rigid pendant with slim canopy QCRP square conduit rigid pendant canopy
STEM LENGTH ²	2 2 feet 3 3 feet 4 4 feet 6 6 feet

ORDERING CODE _____

Follow the steps to specify your fixture, example:
138230 - 3.5 - 15LM - 30K - 90 - SA14 - UNV - DIM10 - WH - RP

LED	POWER
DELIVERED LM	W (90 CRI)
970	14
1250	18

Power Factor ≥ 0.9

- NOTES**
1. Slim canopy with rigid stem connection shall be used in jurisdictions that DO NOT require light fixtures to freely swing in lateral directions, complying with local and national building codes.
 2. Only for RPS canopy.

MOUNTING OPTIONS

Mounting Options

- S** surface mount
- RP** rigid pendant
- RPS** rigid pendant with slim canopy

