

ARRIVE

Wall mounted • Wet location listed



Description:

Arrive LED lanterns feature a die-cast aluminum, powder coated frame and heavily textured glass. One-light small wall lantern. 90+ CRI, 3000K, 623 lumens. Energy Star.

Specifications:

Black (-31) (painted)
Die-cast aluminum construction
Clear Seeded glass panelsDimmable (See Dimming Notes)
Back plate covers a standard 4" hexagonal recessed outlet box
Mounting strap for outlet box included
6" of wire supplied
ENERGY STAR® qualified

Performance:

Number of Modules	1
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	623/69.2 (LM-79)
CCT	3000 K
CRI	90
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed ENERGY STAR® qualified

P6067-3130K9

Images:



Dimensions:

Width: 6"
Height: 8-3/4"
Depth: 7-3/8"
H/CTR: 4" (facing up)

P6067-3130K9**Dimming Notes:**

P6067-3130K9 is designed to be compatible with many Electronic Low Voltage (ELV/Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron Diva DVELV-300P

Lutron Nova T NTELV-300

Lutron Verti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.