

GEOS – model: FM-46

dwelLED™ LED Ceiling Mount

WAC LIGHTING
Responsible Lighting®



FM-4615



FM-4622

Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Cutting-edge technology in the display industry transformed into a super-thin, less than an inch profile flush mount. Multiple mid-powered LED source illuminate the diffuser uniformly and without socket shadows common in conventional flush mounts.

FEATURES

- Edge-lit magic
- Super thin, edge-lit LED panel at less than an inch thick
- High lumen package great for high ceiling applications
- Die-cast aluminum construction
- Wall or ceiling mount with twist-lock mechanism
- Driver located in standard 4" junction box
- Universal driver (120V-220V-277V)
- Color Temp: 2700, 3000K
- CRI: 90
- Dimming: 100% - 10% ELV
- Rated Life: 47,000 hours
- Input: 120 - 277V

SPECIFICATIONS

Construction: Aluminum and White Diffuser Glass

Light Source: High output LED.

Finish: Titanium (TT), White (WT)

Standards: ETL & cETL damp location listed.

ORDER NUMBER

		Color Temp	Watt	Delivered Lumens	Finish
15"	FM-4615-27	2700K	29.5W	1485	TT Titanium WT White
	FM-4615-30	3000K	28.5W	1660	
22"	FM-4622-27	2700K	44.5W	2235	
	FM-4622-30	3000K	42.5W	2375	

Example: **FM-4615-27-TT**

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program.