


All bathtub dimensions are $\pm 1/2"$.

Airbath System II

Blower must be remotely located
(Diagram is required for custom blower connection locations)



LEGEND:

● ON/OFF CONTROL

STANDARD EQUIPMENT:

- PVC Waste & Overflow with Polished Chrome trim
Available with polished brass, polished nickel, satin nickel, oil rubbed bronze or white trim at no additional charge if specified at the time of order. Requests after order is shipped are subject to an up-charge.

INSTALLATION TIPS

- Install according to Owner's Manual and local codes.
- Hot water supply should be 65-75% of tub capacity or greater.
- Always consult your local plumber for recommendations as installations will vary.

DIMENSIONS:

42" x 42" x 33" (1067 x 1067 x 838mm)
Gallon to Overflow = 78 (Liters = 295)

MATERIAL: Interior Acrylic (White & Biscuit Only)
Exterior Acrylic (All Americh standard colors)

TUB FLOOR: Textured

UNDERMOUNT: No

ELECTRICAL REQUIREMENTS

Americh recommends one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bathtub.

OPTIONAL ACCESSORIES

- Chromotherapy
- Dual Color
- Pillow: 12"

CODES AND COMPLIANCE

Americh products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories - Canada (cUL)
- Canadian Standards Association - (CSA)
- ANSI Z124.1 • ANSI A112-19.7 • ANSI A112.19.8

Contact Americh for additional approvals.