# T417000W08



### Design By =

Michele De Lucchi Daniele Moioli

#### Collection =

Outdoor



## Colors & Finishes =



### Materials =

- Pole in extruded aluminum
- Head with lighting module in die-cast aluminum
- Reflector in metallic polycarbonate
- Screen in highly transparent polycarbonate with shock-resistant and anti-UV finish
- Base in painted aluminum

### Specifications —

Delivered lumens	294lm
Light output ratio	19.6lm/W
Power consumption	15W
Led type	14W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	On/Off
Input Voltage	120V
Driver	MEAN WELL - 1 x APC-16-350
BUG Rating	B0-U2-G0

#### Features & Accessories


- Designed for garden or pedestrian lighting
- Base contains holes for ground fixing by means of screws
- Provided with cable and IP68 connector
- Electronic driver integrated
- Standard non dimmable

Packaging =

• For dimming options, please consult with your Artemide Sales Representative

1 x 8-15/16" x 8-15/16" x 40-5/8" / 15.65 lbs - 22.5 cm x 22.5 cm x 103 cm / 7.1 kg

## Dimensions =



Light distribution =

Diffused

11.99 lbs / 5.44 kg

Red = Max Cd. Through Vertical plane
Blue = Max Cd. Through Horizontal plane

Luminaire weight —

Warranty
5 year limited warranty

