

TORRE 14



SCONCES WALL

location: DAMP

SPECIFICATIONS:

DESCRIPTION

Wall-mounted ADA-compliant sconce featuring open-ended handcrafted glass.

LAMPING

Standard: 75W A19 120V incandescent, suitable for dimming.

CFL: 18W 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not

included.

GU24 CFL: Self-ballasted GU24 lampholders. 18W max, 120V, lamp not included.

LED: 10W LED Replaceable source, 120V, dimmable, included.

DIFFUSER

Diffuser shall be handcrafted glass of various decors.

CONSTRUCTION

Glass is secured to the backplate by braided wire. Rectangular backplate (nominal $4"W \times 6.5"H$) shall be constructed of steel, powder-coated white.

METAL FINISH


Decorative metal accents shall be in various finish options.

MOUNTING

Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. Top of glass is approximately 5.5" above the outlet box centerline.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only).





TORRE 14 SHOWN IN COPPER FOIL (8192GF) & SILVER FOIL (8192SF)



For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 10/14



TORRE 14

SCONCES WALL

ORDERING:

FIXTURE/DECOR	- LAMP OPTIONS -	- METAL FINISH	- OPTIONS
819207 White	(blank) 75W A19 Incan	BK Black	LW Low Wattage
8192CF Copper Foil	E1 18W Quad 120V	BR Bronze	labeling
8192CH Cherry	N1 18W Quad 277V	PN Polished Nickel	
8192GF Gold Foil	GU24 18W GU24 120V	SN Satin Nickel	
8192KR Chalk	LED 10W LED 120V,	WH White	
81920K Oak	dimmable		
8192SF Silver Foil			
8192TN Titan			

Ex. 8192CH-SN

Torre 14 Wall Sconce w/ Cherry Glass, Satin Nickel Finish

LED SCONCES:

- Internal driver integrated in the lamp, GU24 base
- Total power of only 10 watts
- Dimmable with a standard dimmer
- Rated life: 30,000 hours
- Frosted acrylic diffuser
- 800 lumens
- CCT: 2800° Kelvin
- CRI: 80+

Project Information:					