

## **ASSEMBLING & INSTALLATION INSTRUCTIONS**

The drawing shown may not exactly match the product enclosed. However, the installation instructions do apply to this product.

## 4744

- **♦** WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.
- **♦** ATTENTION! COUPER LE COURANT AU FUSIBLE OU UN DISJONCTEUR.


## **ASSEMBLING THE FIXTURE (Fig.1)**

- 1. Shut off the power at the circuit breaker box. Remove old fixture and all hardware from Junction Box.
- 2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
- 3. Raise the candle sleeve(F) inset cup of the lamp holder.
- Install the light bulbs (No Included) in accordance with the fixture's specifications. DO NOT EXCEED THE MAXIMUM WATTAGE RATING!
- 5. Attach the column(A) onto the top coupling of the lamp body(E), by turning it clockwise until tight. Attach the arm(B) mounted onto the top lamp body of side, lock it securely with the ball nut(C) and finial(D).
- 6. Attach the assembly lamp body onto the post (no included) and lock it securely with the screw(H).

## **CONNECTING THE WIRES (Fig.2)**

- 1. Connect the electrical wires as follows. Connect the Black wire from the fixture to the black house (hot) Wire. Connect the white wire from the fixture to the white (neutral) house wire. Make sure all wire nuts are secured. You may wrap the connections with electrical tape. If your outlet box has a ground wire (green or bare copper) connect fixture's ground wire to it. Otherwise attach the bare copper fixture wire to the green ground screw on the mounting plate.
- 2. Tuck the wire connections neatly into the wall junction box.

Your installation is now complete Return power to the junction box and test the fixture.



Thank you for purchasing a **LIVEX** product.

Need assistance with parts or assembly? Please call customer service at: 800-761-8056

Or visit us on-line at: WWW.LIVEXLIGHTING.COM