

# ENDORSE

Wall mounted • Wet location listed



## Description:

Endorse celebrates the traditional form of a gas-powered coach light with illumination from an LED source. A die-cast aluminum, powdered coated frame created an intriguing visual effect with the clear beveled glass. An optional fluted glass column is offered as an accessory (P8775-31). 3000K, 90+ CRI, 623 lumens.

## Specifications:

Black (-31) (powdercoat)  
 Die-cast aluminum construction  
 Clear glass beveled panels, Clear beveled panels glass  
 Dimmable (See Dimming Notes)  
 Back plate covers a standard 4" hexagonal recessed outlet box  
 Mounting strap for outlet box included  
 6" of wire supplied  
 ENERGY STAR® qualified

## Performance:

Number of Modules	1
Input Power	9w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	623/69.2 (LM-79)
CCT	3000 K
CRI	90
Life (hours)	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed ENERGY STAR® qualified

## P6057-3130K9

## Images:



## Dimensions:

Width: 8-3/4"  
 Height: 14-3/4"  
 Depth: 9-3/4"  
 H/CTR: 4" (facing up)

## P6057-3130K9

### Dimming Notes:

---

P6057-3130K9 is designed to be compatible with many Electronic Low Voltage (ELV/Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls.

### Dimming Controls

---

Lutron Diva DVELV-300P

Lutron Nova T NTELV-300

Lutron Vienti VTELV-600

Lutron Ariadni AYCL-153P

Lutron Diva DVCL-153P

Lutron Maestro MAELV-600

Lutron spacer/system SPSELV-600

Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.