Thank you for purchasing this quality product. Be sure to check all packing material carefully for small part that may have come loose inside the carton during shipment.



Thank you for purchasing this quality product. Be sure to check all packing material carefully for small part that may have come loose inside the carton during shipment.



(H)

No.	Description	Sketch	Quanlity		
А	Arm Panel L/R		2PCS		
В	Bun Foot	Ċ	4PCS		

PART LIST : WF295782						
No.	Description	Sketch	Quanlity			
С	Headboard panel		1PC			
D	Side Rail		2PCS			
Е	Center Support Slat		1PC			
F	Slats Rolls		2SET			
G	Trundle Cushion		2PCS			
Н	Trundle Side		2PCS			
Ι	Trundle Back		1PC			
J	Trundle Support Slat		1PC			

HARDWARE LIST : WF295781							
No.	Description	Sketch	Size	Quanlity			
K	Washer Semicircle		Ø <u>5</u> "*25L	4PCS			
L	Thread Bolt	0	$\emptyset \frac{5}{16}$ "*2- $\frac{3}{4}$ "L	8PCS			
Μ	Flat Washer	0	$Ø \frac{5}{16}$ "	4PCS			
Ν	Hexagonal Nut		$\emptyset \frac{5}{16}$ "	8PCS			
0	Open Wrench		M12	1PC			
Р	Allen Key		$M4*2-\frac{1}{2}"L$	1PC			
Q	Screw		$Ø 8*1 - \frac{1}{4}$ "L	40PCS			

TOOLS REQUIRED (Not provided)

T)+

⇒ Screwdriver

PAGE 2 OF 6

MADE IN VIETNAM

G

Thank you for purchasing this quality product. Be sure to check all packing material carefully for small part that may have come loose inside the carton during shipment.



Step 2. Before performing this step, please loosen the bolts of the Arm Control Panel L/R(A), intended to hook metal Rail(D) and metal center(E) securely set to the bolt. Besides, pay attention to also bring the Headboard panel(C) which has pre-drilled holes at both ends, to the L/R Arm(A) with two pre-assembled threaded rods, by using the Flat Washer (M), Hex Nut(N). Finally, tighten them with the Allen Key(P), the Open Wrench(O) as guide.



Thank you for purchasing this quality product. Be sure to check all packing material carefully for small part that may have come loose inside the carton during shipment.

Step 3. Note: before placing the pre-assemble clusters Slat roll(F) in the side rails(D), it is advisable to check the direction of the arrow, place it straight out ahead and arrange it neatly. Then, tighten they are by Screws(Q).





PAGE 4 OF 6

Thank you for purchasing this quality product. Be sure to check all packing material carefully for small part that may have come loose inside the carton during shipment.

Step 5. Place the Trundle side plate(H) with mount wheels to put the back face Trundle Cushion(G) and the inner face Trundle back(I), which has four pre-assembled threaded rods, by using the Washer Semicircle(K), Hex Nut(N). Finally, tighten them with the Open Wrench(O) as guide.



Step 6. Place put the Trundle support slat(J) with mount wheels the into the Trundle side(H). Then, put the Slat roll(F) and arrange it neatly. Finally, all togethertighten they are by Screws(Q) as guide.



Thank you for purchasing this quality product. Be sure to check all packing material carefully for small part that may have come loose inside the carton during shipment.

