Euro Style Suex Rose Gold Plated Sink Faucet Dual Crystal Handles



INSTALLATION INSTRUCTIONS



When installing the faucet, push it toward the front of the hole.



15/16"-17/16

3













Install the drain pull rod.

English

Place the faucet and centering ring(s) on the mounting surface.

If the mounting surface is less than 3/16" thick, trim the centering ring.

Install the washer and the mounting collar.

English

Tighten the collar using a flat head screwdriver.

Connect the supply hoses to the stops.

Use two wrenches, as shown, to keep the hoses from twisting.



Remove the aerator.

Flush the faucet for at least two minutes.

Replace the aerator.



Do not overtighten the aerator, or damage may result.



Petroleum-based plumbers putty can damage the surface of some sinks. Please consult the manufacturer of the sink regarding compatible

Cleaning Recommendation

Modern bathroom faucets, kitchen faucets and shower products are made from different materials to comply with the needs of the market with regard to design and functionality. To avoid damage to the product, it is necessary to take proper care of it.

For best results:

- Prevent the buildup of mineral scale and /or soap residue by cleaning your Hansgrohe product(s) when needed.
- Select a cleaning agent specifically intended for the type of product.
- Do not use these types of cleaners as they will cause damage to your Hansgrohe product:
 - × Any cleaning agent containing hydrochloric acid, formic acid, lye, or acetic acid.
 - Abrasive cleaning powders, pads, or brushes. ×
 - × Steam cleaners.
 - "No rinse" cleaning agents. ×
 - Always follow the instructions provided by the manufacturer of the cleaning agent.
- Do not mix cleaning agents, unless directed by the manufacturer.
- Do not spray cleaners directly onto the product as drops could enter openings and gaps and cause damage. When using spray cleaners, spray the cleaner onto a soft cloth or sponge.
- Always rinse your Hansgrohe product thoroughly with clear water and polish dry with a soft cloth after cleaning.

Important

- Residue from soaps and shampoos can cause damage. Rinse the product with clean water after each use.
- Residue from basin/tub/tile cleaner can cause damage to faucets and fittings. Immediately rinse any overspray from the Hansgrohe product.
- Damage to the product caused by improper care or the use of improper cleaning agents is not covered by the warranty.
- If a component of the product is damaged, replace it, as there is risk of injury. .

This General diagram and installation instructions are not intended for any specific

model, but is presented as a general guideline for Installations!