Cuneo wall/floor white T082908

SPECIFICATIONS

	Design By	Specifications	
	Klaus Begasse	Delivered lumens	716lm
		Light output ratio	44.75lm/W
	Collection	Power consumption	16W
Colors & Finishes	Outdoor	Led type	15W Array*
		CCT (Correlated Color Temperature)	4000K
		CRI (Color Rendering Index)	>80
	(B) (B) (B)	Life expectancy	50000Hrs
		Control type	On/Off
_		Input Voltage	120V
White RAL9002		Driver BUG Rating	MEAN WELL - 1 x LPC-20-700 B0-U4-G0
Naterials			
Body in aluminum Prismatic screen in PMMA		 Features & Accessories In wall installation, light can point upwards or downwards Electronic driver integrated Beam: 36 degrees Standard non dimmable For dimming options, please consult with your Artemide Sales Representative 	
mensions		Packaging 1 Box 1 x 12-11/16" x 5-3/16" x 12-1/8" / 4.96 lbs - 32 cm x 13 cm x 30.5 cm / 2.25 kg	
7 ⁷⁸ 20 cm 17 cm			
ight distribution	Luminaire weight 3.97 lbs / 1.8 kg		
	Warranty 5 year limited warranty		

Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane

last updated: 2020-06-30

