

## INSTALLATION REQUIREMENTS:

Fan must be attached to a securely anchored electrical junction box capable of withstanding a load of at least 35 lbs.

## **ELECTRICAL REQUIREMENTS:**

Requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

## **MOTOR SPECS:**

100 x 30 DC motor is designed for optimal performance with this fan.

#### BLADES:

A set of three 24" composite blades is included.

#### **CONTROL OPTIONS:**

Three fan speeds pull chain control included. The reverse switch is located on the switch housing.

# LIGHTING OPTIONS:

One 18-watt LED included. ON/OFF and dimmable pull chain control.

## DOWNROD OPTIONS:

Fan comes with 1" dia. x 6" long wet-location downrod (DR1SS-6). Optional wet-location downrods are available in 12", 18", 24", 36", 48", 60", and 72" lengths. A downrod coupler is available for installations requiring a downrod longer than 72". Fan can be mounted on a sloped ceiling up to 27°. Most sloped ceiling installations require a standard 18" downrod or longer downrod. Optional sloped ceiling ball kits (SCB1-52) are available for slope angles greater than 27° and up to 42°. Optional close-to-ceiling kit is available as well — sold separately. Call technical support for more information.

## LOCATION USE:

Fan is rated for dry, damp and wet locations. This fan is for room up to 400 sq ft.

		Fan w/72" downrod	82.91″	76.24″			
Available Finishes							
BLW	N Black with Black Blade						
MWW	MWW Matte White with Matte White Blade						
SLW	Silve	er with Silver Blade					

Ai	Airflow / Energy Efficiency Info (120V)					
Fan Speed	Max RPM	CFM	CFM / Watts	Amps	Watts	
High	168	5874	190	0.47	31	
Med	111	3723	419	0.17	9	
Low	53	1764	832	0.07	2	

	Energy Guide FTC					
Power (W <sub>ave</sub> )	Total Air Delivery (CFM <sub>ave</sub> )	Estimated Yearly Energy Cost (\$)	Ceiling Fan Efficiency (CFM/W)			
19	3649	5	188			