

## Lighting Your Life Since 1970

Product Specifications - 10044FTOI			
Job Name:	Job Type:		
Quantity:	Comments		



## 10044FTOI

**Logan 3-Light Pendant** 

Finish	Glass/Shade	<b>Product Category</b>
Oil Rubbed Bronze	Frosted	Invert Bowl Pendant

3

Lamping
Number of Bulbs
Light Type
Bulb Type
May Dulle Wetters

Light Type	Incandescent
Bulb Type	MB
Max Bulb Wattage	100
Max Fixture Wattage	300
Rated Life	
Rated Lumens	±0
Color Temp	
Bulb(s)	Not Included
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast/Driver/Transformer	No
Dimmable	Standard Dimmer

Measurements	
Width	15.0"
Height	21.0"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	6.0 lbs
Height Adjustable	N/A
Slope	N/A
Chain Length	N/A
Wire Length	N/A
Canopy Width	N/A
Canopy Height	N/A
Canopy Length	N/A

	Shipping	
"	Carton Weight	6.0 lbs
"	Carton Width	18'
٩	Carton Height	11'
٩	Carton Length	18'
٩	Carton Cubic Feet	1.86
٩	Master Pack	1
4	Master Pack Weight	N/A
4	Master Pack Width	N/A
4	Master Pack Height	N/A
s	Master Pack Length	N/A
4	Master Cubic Feet	N/A
٩	UPS Shippable	Yes

Certification		Other		Equivalents	
Safety Rating		UPC Code	783209030435	Incandescent Watts	N/A
Energy Star	No	Shades Included	N/A	Fluorescent Watts	N/A
CA Title 24	No	Crystals Included	N/A		
CA Title 20	No	Diffuser Included	N/A		
ADA	No	Conversion Kit	N/A		
Dark Sky	N/A	Material	N/A		

Maxim Lighting International and all designs, logos and images © 2013 Maxim Lighting International. All Rights Reserved. Maxim Lighting International reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes.

Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.