

Customer Service : (702)361-4345, (800)525-2655, customer.service@kalco.com

WARNING - TO REDUCE THE RISK OF FIRE OR INJURY:

1. If you are unfamiliar with electrical wiring, call a qualified electrician to install this unit. More than one person may be necessary to install fixture, make sure you have enough qualified help.
2. Turn off the power to the fixture's circuit at the service panel. Use a voltage detector to verify that the power is off.
3. DO NOT install bulb which exceeds the maximum wattage specified on the socket label.

FRAME INSTALLATION


Step 1. Screw Crossbar 2 to outlet box 1 with original outlet box screws. Make sure crossbar studs are pointing away from wall.

Step 2. Get fixture frame a few inches close to wall and connect wires: Connect fixture ribbed wire to power supply black wire. Connect fixture smooth wire to power supply white wire. Connect fixture silver or copper bare wire to power supply green wire.

Step 3. Align fixture back plate holes to crossbar studs 2 and fix it flat to wall, secure fixture with decorative nuts 4, then Install light bulbs.

Step 4. Install threaded rod 5 to bottom of fixture, then install parts 6, 7, 8 and 9.


Proceed to install crystal set; follow directions on pages 2 and 3.



Customer Service : (702)361-4345, (800)525-2655, customer.service@kalco.com


CRYSTALS SHAPES AND CODES

63MM 82745




A

63MM 82745




B1

50MM 82745




B2

50MM 82745




C

50MM 82745



D



701 40MM

E

