<ul> <li>-Attach the ground wire to the cross bar with a green ground screw.</li> <li>Carefully tuck wire back into the OUTLET BOX</li> <li>4, Place the Back plate against the Outlet box, secure with the Ball nut.</li> <li>5, Put the end finial onto the fixture and screw it.</li> <li>6, Put the Glass (GLASS SOLD separately ) onto the Socket and screw with the Ring .</li> </ul>	<ul> <li>Screw-1.</li> <li>2, Attach the Cross Bar to the Outlet Box by 2pcs Mounting Screws.</li> <li>3, Make wire connections: <ul> <li>-Smooth wire (w/marking) from the light to black wire from power source.</li> <li>-Ribbed wire (w/o marking) from the light to white wire from power</li> </ul> </li> </ul>	ASSEMBLY AND INSTALLATION 1, Thread the Screw-1 to the Cross bar, then screw the Hex nut on the	All electrical connections must be in accordance with local and National Electrical Code(N.E.C) standards.If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician. Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustrations on the installation instructions.	Turn off the main power at the circuit breaker before installing the fixture,in order to prevent possible shock.	Please read carefully and save these instructions,as you may need them a later date.	WALL SCONCE FIXTURE INSTALLATION INSTRUCTIONS
ITEM NO:162-DG 163-DG 164-DG			MOUNTING SCREW BLACK WIRE WHITE WIRE GROUND WIRE	BALL NUT GLASS	SOCKET	REW-1 CROSS BAR

•

۱. Million