




Screw and Expansion screw

Assembly Instructions



Check the wall on which you want to hang the mirror to ensure it is a load-bearing wall so that it can support the weight of mirror.

Measure distance between centers of two hooks (Flexible rule is recommended as the tool).

1

2

Mark the centers of hooks on the wall: Measure the width and height of the wall you choose with flexible rule, and mark the location of two centers of hooks with a pencil.

Drill at the marked place with prepared percussion drill whose broach is with a diameter of 6mm-8mm, and the holes drilled should be about 5cm deep.

3

4

Knock expansion screws into the holes drilled with hammer.

Screw screws into expansion screws with a screwdriver, and keep the top of screws 5mm away from the wall (A plier required to screw 7-shaped hooks).

5

6



FUNCTION INDICATOR



SHORT PRESS THE SWITCH: OPEN AND CLOSE THE LIGHT/SWITCH THREE LIGHT COLORS

LONG PRESS THE SWITCH: STEPLESS ADJUSTMENT OF LIGHT BRIGHTNESS/TURN ON HUMAN INDUCTION



SHORT PRESS THE SWITCH: SWITCH THREE LIGHT COLORS

LONG PRESS THE SWITCH: TURN ON HUMAN INDUCTION



IN THE BLUE LIGHT STATE, LONG PRESS THE SWITCH



IN THE BLUE LIGHT STATE, LONG PRESS THE SWITCH



BLUE LIGHT FLASHING: CLOSE THE INDUCTION FUNCTION