

FLURRY & FLURRY-HV

Variable Drive, Dual 10" Fans



5 Year Limited Warranty
Covers Components



Lifetime Warranty
Covers Housing



FLURRY SERIES

The COOL-SPACE FLURRY Series is the ideal solution to cool workshops, service centers, industrial spaces, outdoor venues, decks and patios. Using just a garden hose and standard electrical outlet, the COOL-SPACE FLURRY Series greatly reduces temperatures in any well ventilated space. When more cooling is needed, two FLURRY units can be stacked. No additional floor space with twice the cooling capacity!

This attractive, low profile portable evaporative cooler series is built for your comfort with quality components that are backed by a 5 year limited warranty.

FLURRY

The FLURRY unit is designed to have minimal impact visually and maintain low sound levels to ensure a pleasant ambience. The FLURRY is uniquely suited for patios, restaurants and other open-air venues.

FLURRY-HV

The FLURRY-HV is designed with high output in mind. Its performance level makes it better suited for industrial and automotive applications.

- Aesthetically pleasing design
- Up to 800 sq. ft. of cooling coverage per unit
- Use indoors or outdoors in any well ventilated space
- Stackable configuration to customize your cooling needs
- Built-in, 8 gallon water reservoir for stand alone use
- Swivel, locking casters for easy maneuvering
- Low water indicator light
- Low water shut-off to extend pump longevity
- Tough, thick UV resistant, durable roto molded polyethylene housing
- Directional louvers
- Drain plug for easy water removal
- Pad protecting grilles for increased pad durability and aesthetics
- High Efficiency cooling media

💧 Fill Up 🔌 Plug In ❄️ Cool Down

FLURRY

CS6-210



Power Supply	110V/1ph/15A minimum branch circuit
Fan Amperage	1.1
Fan Motor	High efficiency, totally enclosed .174hp/110V/60Hz, Variable Speed
Fan Size (qty)	10" (2)
Airflow	1200 cfm
Cooling Coverage	600 sq. ft.
Cooling Media	4" thick, high efficiency, cross corrugated, angle fluted
Water Supply	Garden hose connection or portable supply tank. Water level regulated by a float valve. Maximum pressure 120 psi
Water Reservoir	Internal 8 gallon capacity
Unit Dimensions	24" wide x 24" deep x 34" high
Unit Weight	51 lbs

FLURRY-HV

CS6-210-HV



Power Supply	110V/1ph/15A minimum branch circuit
Fan Amperage	1.9 A
Fan Motor	High efficiency, totally enclosed .32hp/110V/60Hz, Variable Speed
Fan Size (qty)	10" (2)
Airflow	1800 cfm
Cooling Coverage	800 sq. ft.
Cooling Media	4" thick, high efficiency, cross corrugated, angle fluted
Water Supply	Garden hose connection or portable supply tank. Water level regulated by a float valve. Maximum pressure 120 psi
Water Reservoir	Internal 8 gallon capacity
Unit Dimensions	24" wide x 24" deep x 34" high
Unit Weight	51 lbs