

# PLEASE REVIEW PRIOR TO INSTALLATION

---

## FEATURES/SPECIFICATIONS

---

Latex / Nylon-reinforced, wet-strength paper, 11 mil  
97% Opacity  
Durable, high tear strength  
Meets ASTM 793 standards for commercial wallcovering  
Low wet expansion  
Class A Fire Rating

---

## INSTALLATION GUIDELINES

---

### Wall Prep

Walls should be prepped to a smooth, clean, and dry surface prior to installation. Mural-Pro will not hide wall flaws. Primer sealer should be used on unpainted drywall. Prime over glossy painted walls.

\* Primer sealer should be used on unpainted drywall, or over previously applied glossy paint. Use acrylic wall-covering primers: Professional Ultra Prime (PRO-977), Golden Harvest White Bite, or Allpro Ultra Prep 685. Priming provides a sound surface that wallcovering will adhere to. It is recommended to strip down previous layer(s) of wallcovering. The wallcovering may seem to be firmly adhered to the wall, but the addition of another layer can cause adhesion failure.

### Paste

Use clear adhesives such as: Professional Ultra Premium Heavy Duty Clear Strippable (PRO-880), Golden Harvest GH-34 Clear Strippable, and Allpro Pro-Duty 3400. Clay adhesives may also be used (PRO-732, PRO-774, Golden Harvest GH-40, Allpro Extra Strength Vinyl 600 & 661). For more permanent wallcoverings, use Professional heavy Duty Clear PRO-838 or Allpro Clear Hang 610. Apply a coat of the desired adhesive using a 1/2" nap paint roller.

### Hanging

**Do not** use tape on the image surface. **Do not** get paste on image surface. **Do not** apply water to the image surface as it may cause discoloration. Trim white margins to image edge. Apply paste to the back with a roller on a clean surface. Align the top and adjoining edges. Smooth panels into place using a smoothing brush, starting at the center of the panel working toward the edges. Push out any air pockets using the smoothing brush.

### Sealing

Mural-Pro may have a protective coating or liquid laminate applied to protect it and extend life. Always pretest laminates prior to use for compatibility. Pressure-sensitive laminates are not recommended. We offer this service prior to delivery, adding up to 2 weeks lead-time. (**Pricing** - \$8 per yard, \$139 minimum per order.)

**We gladly provide sample pieces for test hanging upon request.**

---

### DISCLAIMER

*No claims will be accepted for inadequate or faulty installation based on these instructions, nor will claims be accepted for cut or installed wallpaper.*

---

For more information, call 1-540-337-6494, or visit our website: [www.MuralSources.com](http://www.MuralSources.com)