Logico Garden triple floor

T416700W08

SPECIFICATIONS



Design By Michele De Lucchi Daniele Moioli

Collection =



Specifications = **Delivered lumens** 294lm Light output ratio 19.6lm/W Power consumption 15W 14W Array* Led type CCT (Correlated Color Temperature) 3000K CRI (Color Rendering Index) >80 Life expectancy 50000Hrs Control type On/Off 120V Input Voltage MEAN WELL - 3 x APC-16-350 Driver BUG Rating B0-U2-G0

Pole in extruded aluminum

Materials =

Colors & Finishes

Anthracite grey

- Head with lighting module in die-cast aluminum
- Reflector in metallic polycarbonate
- Screen in highly transparent polycarbonate with shock-resistant and anti-UV finish
- Base in painted aluminum

Features & Accessories

• Designed for garden or pedestrian lighting

- Base contains holes for ground fixing by means of screws
- Provided with cable and IP68 connector

Electronic driver integrated

• Standard non dimmable

Packaging =

• For dimming options, please consult with your Artemide Sales Representative

Dimensions -



Light distribution -

Diffused



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane

Luminaire weight 35.32 lbs / 16.02 kg

Warranty 5 year limited warranty

4 Boxes

1 x 15-13/16" x 15-13/16" x 4" / 8.11 lbs - 40 cm x 40 cm x 10 cm / 3.68 kg

1 x 9-15/16" x 9-15/16" x 28-5/8" / 10.58 lbs - 25 cm x 25 cm x 72.5 cm / 4.8 kg

1 x 9-15/16" x 9-15/16" x 28-5/8" / 12.13 lbs - 25 cm x 25 cm x 72.5 cm / 5.5 kg

1 x 8-15/16" x 8-15/16" x 40-5/8" / 15.65 lbs - 22.5 cm x 22.5 cm x 103 cm / 7.1 kg

last updated: 2020-06-30

We reserve the right to change specifications of our products. For the latest product information please visit www.artemide.net

Artemide