DOUBLE SPOT Endurance Wallpack

WAC LIGHTING

Responsible Lighting®

+	Fixture Type:				
	Catalog Number:				
	Project:				
	Location:				
	SPECIFICATIONS Construction: Die-cast aluminum				
Max 12½" Max 6½"	Power: Line Voltage input (120V)				
PRODUCT DESCRIPTION	CRI: 85				
Die cast aluminum factory sealed housings with patent pending design for	Dimminer 100% 10% with Electronic Low Voltage (ELV) dimmer				

Di a water and dust proof IP66 rated outdoor luminaire

FEATURES

- IP66 and ETL & cETL Wet Location Listed
- Factory-Sealed LED Light Engine
- Energy Star[®] rated
- Die-Cast Aluminum Construction
- 120V Direct Wire No Driver Needed
- Photo/Motion Sensor Sold Separately
- Smooth and Continuous ELV Dimming

Dimming: 100% - 10% with Electronic Low Voltage (ELV) dimmer Finish: Architectural Bronze, Graphite and White Standards: Energy Star®, IP66, Wet Location, ETL & cETL Listed Operating Temperature: -40°C (-40°F) to 40°C (104°F) Rated Life: 43,000 hours

PHOTOMETRY



ORDER NUMBER

	Power	Comparable	Colo	or Temp	Delivered Lumens	CBCP	Finish	
WP-LED430	30W	150W Halogen	30 50	3000K 5000K	965 x2 1030 x 2	550 x2 585 x2	aBZ aGH aWT	Architectural Bronze Architectural Graphite Architectural White

Example: WP-LED430-30-aWT

ACCESSORIES

Motion Sensor (120V)	MS-120-GY Gr	ronze iray Vhite		Photocell Sensor (120V)	PC-120-BZ PC-120-GY PC-120-WT	Bronze Gray White
-------------------------	--------------	------------------------	--	----------------------------	-------------------------------------	-------------------------

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. OCT 2016