



Quick Startup Guide

Brio CLBL420 Essential Series Bottom-Load Water Cooler

STYLISH - CONTEMPORARY - CONVENIENT

1

READ ALL DIRECTIONS BEFORE PLUGGING IN DISPENSER.

Important: Do not plug in dispenser until step 4. This guide is a general reference to help you quickly and easily set up your Brio water cooler.

2

SET COOLER IN DESIRED LOCATION.

Ensure cooler is located on a level floor, out of direct sunlight and at least 4 inches from a wall.



3

INSERT WATER BOTTLE.

Use the slot on the right-hand side of the cooler to pull the door open. Wipe bottle cap with paper towel. Peel the label off the 5-gallon bottle. Remove the bottle probe from inside the cooler. Insert probe into bottle, slide the bottle into cooler and close the door. (Please wear gloves when setting up or replacing water bottles.)

4

PLUG IN DISPENSER.

Dispenser should always be installed within 6 feet of a power source. Dispenser should be plugged into a GFCI electrical outlet. Do not use extension cords. Ensure hot tank switch on back of unit is in the Off "O" position prior to plugging in.



5

PURGE WATER TANKS.

The Brio CLBL420 has a self-priming feature that takes approximately 5 minutes to fill both the hot and cold tanks. After that time, dispense water from both the hot and cold tanks to confirm that they have filled.

6

TURN ON HOT TANK SWITCH.

Once the hot tank has been primed, turn on the hot tank switch that is located on back of the cooler. Water will reach 186° F within 5 minutes.



7

INSERT DRIP TRAY.

Push the drip tray into the pocket above the metal clip on the machine to snap it together.

WARNING TO

USERS AND PARENTS:

Adult supervision required.
Equipment dispenses very hot water.

ESSENTIAL
COOLER SERIES



HOT, ROOM & COLD



BOTTOM-LOAD



UL LISTED



ENERGY STAR



NSF / ANSI 372