

# Kathryn<sup>®</sup> Comfort Height<sup>®</sup>

One-piece compact elongated chair height toilet

K-3940

#### Features

- One-piece toilets integrate the tank and bowl into a seamless, easy-to-clean design.
- Compact elongated bowl offers added room and comfort.
- Comfort Height® feature offers chair-height seating that makes sitting down and standing up easier for most adults.
- 1.28 gpf (4.8 lpf).
- Concealed trapway and Clean Caps® facilitate easier cleaning and enhanced design.
- Standard left-hand Polished Chrome trip lever included.
- Glenbury<sup>™</sup> Quiet-Close<sup>™</sup> seat with Quick-Release<sup>™</sup> functionality allows seat to close quietly and quickly unlatch from the toilet for easy removal and convenient cleaning.
- Coordinates with other products in the Kathryn collection.

# Technology

- Single-flush gravity uses the force of gravity and a precision-engineered tank, bowl, and trapway to create a strong siphon during flushing.
- AguaPiston<sup>®</sup> canister allows water to flow into the bowl from all sides (360 degrees), increasing the power and effectiveness of the flush.
- Flush valve's 3:2 ratio harnesses the natural force of gravity and optimizes flush performance.
- Durable canister design has 90% less exposed seal material than a 3" flapper for leak-free performance.
- Light-touch canister flush requires a lower actuation force than a flapper.
- AquaPiston<sup>®</sup> canister flush valve optimizes flush performance and resists warping and deterioration.

### Installation

- Standard 12" (305 mm) rough-in.
- Supply line sold separately.

### Water Conservation & Rebates

Eligible for consumer rebates in some municipalities.

#### **Recommended Products/Accessories**

K-75796 Cachet® Nightlight Quiet-Close™ Elongated Toilet Seat K-4108 C3®-230 Elongated cleansing toilet seat K-9131 Trip Lever 1023457 Wax Ring/Hardware Kit 1265114 Connector Hose K-23726 Drain treatment





### Codes/Standards

ASME A112.19.2/CSA B45.1 EPA WaterSense® ADA ICC/ANSI A117.1 CSA B651 OBC

# KOHLER<sup>®</sup> Toilets and Seats Limited Warranty

See website for detailed warranty information.

# **Available Colors/Finishes**

Color tiles intended for reference only.

lor	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune

Co

- Ice<sup>™</sup> Grey 95
- G9 Sandbar





# Kathryn<sup>®</sup> Comfort Height<sup>®</sup>

One-piece compact elongated chair height toilet K-3940



### **Technical Information**

All product dimensions are nominal.			
Toilet type:	One-piece		
Waste Outlet:	Floor		
Bowl shape:	Elongated		
Flush type:	AquaPiston®		
Trap passageway:	2-1/8" (54 mm)		
Water Consumption			
Full:	1.28 gpf (4.8 lpf)		
Water surface size:	10-1/2" x 7-1/2" (267 mm x 191 mm)		
Rim to water surface:	5-5/8" (143 mm)		
Rough-in:	12" (305 mm)		
Seat-mounting holes:	5-1/2" (140 mm)		

# **Fixture Supply Requirements**

Min static pressure:	20 psi (137.9 kPa)
Max static pressure:	80 psi (551.6 kPa)
Min flowing pressure:	15 psi (103.4 kPa)
Min flow rate:	1 gpm (3.8 lpm)

### Notes

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a  $45^{\circ}$  double wye fitting.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

Accessibility standards may require controls to be located on the open side of the toilet.

