ASSEMBLY INSTRUCTIONS

(For LD17863F-28*50)


ATTENTION:

- 1. Please read these instructions carefully before assembly.
- 2. Since aluminum is soft metal over tightening may strip thread or break the part.
- 3. DO NOT use power tools.
- 4. Check parts against the parts list to make sure you have all parts needed for proper assembly.
- 5. Familiarize yourself with the inventory of parts and the accompanying illustrations to ensure safe and proper assembly.

Assembly step:

- Put the top(A) on a soft surface, then loosely attach the leg(B) to the top with the flat washer(E), lock washer(F), bolt(D) and PVC cover(G).
 Do not over tighten.
- 2. Tighten all the bolts and fasten firmly.

Warning: DO NOT use acid or alkaline washing liquid to clean the product.





| Parts list | Parts picture | Description | Q'ty | Parts list | Parts picture | Description | Q'ty |
|------------|---------------|-------------|---------------------------------|------------|---------------|-------------|------|
| Α | | Seat | 1 | D | (M6*40) | Bolt | 8 |
| | | | | E | | Flat washer | 8 |
| В | | Leg | 2 | F | 0 | Lock washer | 8 |
| С | 4 | PE cap | Factory already assembled | G | (3) | PVC cover | 8 |
| | | | | Н | | Wrench | 1 |

***DO NOT OVER TIGHTEN**

Made in China

* NO POWER TOOLS





