

Design By

Carlotta de Bevilacqua

Collection =

Design



standard length min. 19 ^{3/4}" - max. 78 ^{3/4}" min. 50 cm - max. 200 cm extended length min. 19 ^{3/4}" - max. 216 " min. 50 cm - max. 548 cm

Colors & Finishes =



Features & Accessories

Specifications =

Delivered lumens

Light output ratio

Life expectancy

Control type

Input Voltage

Driver

Led type

Power consumption

CCT (Correlated Color Temperature)

CRI (Color Rendering Index)

• 9 concentric mobile ellipses obtained by an aluminum plate support a circuit of 384 LEDs

2549lm

30W 28W Array*

3000K

50000Hrs

120-277V

Dimmable 2-Wire

ADVANCE - 1 x XI050C100V054XPL1

>80


84.97lm/W

- The ellipses rotate independently on two different axes enabling light to be directed
- Numerous spatial configurations can be obtained by adjusting the rings as needed
- When the device is closed up it is completely flat
- Also compatible with 0-10V dimming

Materials =

• Made in anodized aluminum

Dimensions =




Packaging =

1 Box

1 x 43-13/16" x 28-7/16" x 3-1/4" / 20.06 lbs - 111 cm x 72 cm x 8 cm / 9.1 kg

Light distribution

Direct/Indirect



Warranty =

12.35 lbs / 5.6 kg

5 year limited warranty

Luminaire weight =

Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane