

SOLID FORGED BRASS: Rockwell entrance handle, cylinder collar, knobs, rose, and turnpiece knobs are all manufactured of solid forged brass for precision, extra strength and long lasting durability.

ANSI Standard: Tested to ANSI 156.2 Series Grade 2

LATCHES: Rockwell entrance handle Latches are constructed for mechanical durability and smooth operation. The heavy latch bolt springs are cycle tested to eliminate lever sag. All latches are reversible with an added reversible latch bolt feature for ease of installation.

BACKSET: Adjustable deadbolt /latches with 2-3/8" or 2-3/4" backset are supplied.

FACEPLATE: Deadbolts and Latches are supplied with a 1" x 2.25" radius faceplate.

Distance between Center of Latch and Deadbolt (CTC) Sectional locksets accommodate any center to center greater than 5-1/2". Non sectional locksets work with 5-1/2" CTC 2-1/8" diameter Double bore.

CYLINDER: supplied with 5 pin bump resistant keying. SC1 Keyway pin depths and increments. Kwikset Keyway are available.

DOOR THICKNESS: 1-3/4". Conversion kits available for 2-1/4" thick doors.

Handing: Product is NON-HANDED. Fits Right or Left Hand doors.

KEYS: Solid Brass Designed with a 1-1/4" wide bow

STRIKE: Latches are supplied standard with a full lip strike.

FUNCTIONS: Entrance (Keyed entry). Dummy conversion kits are available to convert a keyed entry active handle set into a Dummy function handle set. Dummy conversion kits are supplied free of charge on orders of 2 sets for a double door application.

DEADBOLT: UL listed deadbolt latch option.

GRAPHIC INSTALLATION INSTRUCTIONS: Rockwell handle sets are designed for easy installation. Illustrative and graphic instructions make mounting the hardware fast and easy.

Installation and assembly of the product onto a door is required.



Double Bore Specification on the Door is required 2-1/8" diameter and 5-1/2" center to center







