

Always check the website for the most updated specifications: www.americh.com



Builder Series



Platinum Series



Airbath System II



GRAB BAR



- ACCESS PANEL (MINIMUM 16" X 20")

LEGEND: P PUMP в BLOWER 🗢 JET ROTARY JET SUCTION LIGHT ON/OFF CONTROL

INSTALLATION TIPS

- Install according to Owner's Manual and local codes. Always consult your local plumber for recommendations.
- Certain options or altering the pump/blower location may cause the pump/blower to extend beyond the tub decking.
- Airbath III units may be $1 \frac{1}{2}'' 2 \frac{1}{2}''$ taller than stated.
- Hot water supply should be 65-75% of the tub capacity or greater. ٠
- Cut Dimensions: 64" x 30". It is recommended to wait for unit to • arrive before cutting.
- All specifications are subject to change without notice.
- The combination of multiple systems and options may require components to stick out and/or be remotely installed in the field.



Luxury Series



Combination (pump and blower location only)



Airbath System III





All bathtub dimensions are $\pm 1/2''$.

DIMENSIONS

66" x 32" x 22" (1676 x 813 x 559 mm) Whirlpool Operating Gallons = 42 (Liters = 159) Gallon to Overflow = 80 (Liters = 303)

MATERIAL: Acrylic (All Americh Standard Colors)

TUB FLOOR: Non - Textured

UNDERMOUNT: Yes

- Advise Americh when ordering to ensure there are no issues with deck mounted controls.
- Always take dimensions directly from the unit.

ELECTRICAL REQUIREMENTS

Americh recommends one 20 amp ground fault circuit interrupter (GFCI) for each power supply provided with the bathtub.

STANDARD EQUIPMENT:

• Adjustable Feet

OPTIONAL ACCESSORIES

- Apron (++) -Available with Linear or Integral Drain Only
- Chromatherapy*
 Grab Bars: 9" *- 14" 16"
- High Density Insulation*
- iBath Sound System
- Inline Heater (whirlpool only)
- Jets: Additional or Rotary*
- Lo Profile Tub Edge
- Ozone System (whirlpool and/or Airbath only)
- Pillows: Angle* 12"
- Remote Control Upgrade (select series only)
- Serenity Soak (tub only)
- Syllent Pump with Heated Air*
- Thermal Comfort System
- (TCS must be at opposite end if used with VSM)
- Tile Flange Kit Trim Kit Upgrade^{*}
- Vibro Sonic Massage (VSM must be at opposite end if used with TCS)
- Waste & Overflows Upgrades
 - Cable Drive Waste & Overflow*
 - PVC Waste & Overflow⁺ Linear Waste & Overflow
- (*) Standard on Platinum Series
- +) Standard on Luxury Series
- +) Factory installed aprons on this model may increase the overall height of the tub when ordered with certain

CODES AND COMPLIANCE

Americh products meet or exceed the following standards:

- Underwriters Laboratories (UL)
- Underwriters Laboratories Canada (cUL)
- Canadian Standards Association (CSA)
- ANSI Z124.1 ANSI A112-19.7

