

LaSalle LED Outdoor Sconce LASW Series

Features

This LED light is ideal for security and general lighting. 3 in 1 color temperature adjustable option. Decorative metal accents. Provides lighting in residential, commercial, and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Textured grey or textured bronze powder coated finish.

Diffuser

Diffuser is .100" thick matte white acrylic.

Electrical

This unit is direct wired with a low voltage electronic LED driver. The constant current LED driver is rated for 120-277 VAC input, 0-10V dimmable. Minimum starting temp -20°F.

Lamping

Fixture includes LED modules capable of producing: 17" - 24W, 2800 source lumens 28" - 28W, 3300 source lumens 3000K, 3500K, 4000K Adjustable (CCT). Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for wet locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

LOCATION DATE PREPARED BY COMMENTS CATALOG NUMBER DATE DATE QUANTITY FIXTURE TYPE





17″

28″



Ordering Information:

		Source			
Textured Grey	LED	Lumens		H	W D
LASW051728LAJD2TG	24W	2800	3000K/3500K/4000K	17"	5-1/2" 3-3/8"
LASW052833LAJD2TG	28W	3300	3000K/3500K/4000K	28"	5-1/2" 4"
Textured Bronze					
LASW051728LAJD2BZ	24W	2800	3000K/3500K/4000K	17"	5-1/2" 3-3/8"
LASW052833LAJD2BZ	28W	3300	3000K/3500K/4000K	28"	5-1/2" 4"