NFX

Brio LED Sconce BRS Series

Features

Half-round wall mount sconce offers high quality decorative extruded aluminum bands. Open top and bottom for wall wash effect. Fixture mounts to standard junction box (not included).

Construction

Back plate is die-formed of 22-gauge steel. Decorative bands are .060" extruded aluminum with an apparent thickness of .100" that are screwed to a 22-gauge back plate. Power supply connections must be made inside a junction box (not included).

Finish

Available in satin nickel or oil-rubbed bronze finish.

Diffuser

Diffuser is .100" thick matte white extruded acrylic lens that installs from the top and slides into position. Allow 18" from top of fixture to any obstruction to clear lens installation.

Electrical

Input 120-277 VAC 60 Hz. 0.14A at 120 VAC. Compatible with residential (TRIAC/ELV) and commercial (0-10V) dimmers. TRIAC and ELV dimming only at 120VAC.

LED

Integrated LED modules capable of producing: 17W, 1400 source lumens Adjustable Choice 3000K, 3500K, 4000K (CCT). Rated for 50,000 Hrs. 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. ADA

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

Ordering Information:

Satin Nickel

LED Oil-Rubbed Bronze BRS071814LAJUDSN BRS071814LAJUDRB 17W

Source Lumens Adjustable CCT 1400

н w D MC 3000K/3500K/4000K 18" 7-1/4" 4" 9"

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	-









MC - Mounting Center