



|                |  |              |
|----------------|--|--------------|
| LOCATION       |  | DATE         |
| PREPARED BY    |  | QUANTITY     |
| COMMENTS       |  | FIXTURE TYPE |
| CATALOG NUMBER |  |              |

## Boon LED Outdoor Sconce BONW Series

### Features

Decorative metal cut housing. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture mounts to standard junction box (not included).

### Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

### Finish

All metal parts are powder coated in white or black.

### Diffuser

Frosted glass diffuser.

### Electrical

This unit is direct wired with a constant current LED driver rated for 120-277V VAC input, 0-10V dimmable. Minimum starting temp -20°F.

### Lamping

Fixture includes an LED module capable of producing:  
12W = 1000 source lumens  
3000K (CCT). Rated for 50,000 Hrs., 90 CRI.


### Certification

All fixtures are cETLus listed for wet locations.  
ADA

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

**Specifications and dimensions**  
subject to change without notice.



## Ordering Information:

| White             | Black             | LED | Source Lumens | CCT   | H   | W  | D  |
|-------------------|-------------------|-----|---------------|-------|-----|----|----|
| BONW071710L30D2WH | BONW071710L30D2BK | 12W | 1000          | 3000K | 16" | 6" | 3" |