

# **DORIAN 10 / 17**





# location:

### **SPECIFICATIONS:**

#### **DESCRIPTION**

Wall-mounted **ADA-compliant** sconces featuring open-ended handcrafted glass.

#### LAMPING

**Standard:** 60W A19 120V incandescent, suitable for dimming. **CFL:** 4-Pin CFL with non-dimming electronic ballast. 120V, lamp not included.

GU24 CFL: Self-ballasted GU24 lampholders. 13W max, 120V,

lamp not included.

LED: 10W LED Replaceable source, 120V, dimmable, included.

#### **DIFFUSER**

Diffuser shall be handcrafted glass of various decors.

**Dorian 10:**  $5.75''W \times 10.25''H \times 4''D$  **Dorian 17:**  $5.75''W \times 17.5''H \times 4''D$ 

#### **CONSTRUCTION**

Stamped aluminum fitter is powder coated white. Glass is secured to fitter by set screws.


#### **MOUNTING**

Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lamping. 10" fixture is centered on the outlet box. 17" fixture centerline is 0.75" below the outlet box centerline. Can be oriented horizontal or vertical. Wall mount only.

#### **LABELS**


UL or ETL Listed. Suitable for Damp Locations (interior use only).

#### Dorian 10: #1189



FIXTURE/DECOR -		- LA	LAMP OPTIONS		- OPTIONS	
118907	Opal Matte	(blank)	1x 60W A19 Incan	LW	Low Wattage	
118952	Marble	E1	1x 18W Quad 120V		labeling	
118983	Mocha	GU24	1x 13W GU24 120V			
		LED	1x10W LED 120V,			
			dimmable			

## Dorian 17: #1190



FIXTURE/DECOR		- L/	LAMP OPTIONS		- OPTIONS		
119007	Opal Matte	(blank)	2x 60W A19 Incan	LW	Low Wattage		
119052	Marble	H1	1x 26W Quad 120V		labeling		
		Q1	1x 26W Quad 277V				
		GU24	2x 13W GU24 120V				
		LED	2x10W LED 120V,				
			dimmable				

#### Ex. 119007

Dorian 17 Wall Sconce w/ Opal Matte Glass

# Project Information:



DORIAN 17 SHOWN IN OPAL MATTE (119007)

MARBLE

мосна\*





\*Only available as Dorian 10

## **LED SCONCES:**

- Internal driver integrated in the lamp, GU24 base
- Total power of only 10 watts
- Dimmable with a standard dimmer
- Rated life: 30,000 hours
- Frosted acrylic diffuser
- 800 lumens
- CCT: 2800° Kelvin
- CRI: 80+

All dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

**REV 10/14**