

## **Elena Task Lighting ELNU Series**

#### Features

The ELNU series low profile make it ideal for undercabinet lighting in kitchens,

study area and displays. A pivoting light bar will allow for direct light in where needed most. Available in 5 different lengths, ranging from 10" to 40" to handle most application requirements.

· Direct wire option through multiple knockouts

- Pivoting light bar adjustable beam angle Linkable up to 200 Watts Captive mounting screws
- USB-A and USB-C charging ports
- BX/NM cable connector
- Direct connector (included)
- 5 CCT color changing switch

### Construction

Fixture housing is made from extruded aluminum.

#### Finish

All exposed metal parts are painted Black or White.

#### Diffuser

White polycarbonate.

#### Electrical

Input 120V 60 Hz. This product provides a user selectable switch with 5 color choices - 2700K, 3000K, 3500K, 4000K & 5000K CCT respectively. The fixture is dimmable with most standard 2 wire (Triac) wall dimmers or an electronic low voltage dimmer switch (sold separately). USB-A, USB-C charging ports on 14, 22, 32, 40 inch models ONLY.

#### LED

Integrated LED type SMT array, non-replaceable arrays use from 5 to 20 Watts and produce from 300 to 1300 lumens. Create 2700K, 3000K, 3500K, 4000K or 5000K color temps. Rated to 50,000 hrs. 90 CRI.

#### Certification

Fixtures are cETLus listed for indoor damp locations and carry a ETL rating for undercabinet/convertible/linkable mounting. ENERGY STAR® qualified Title 24/JA8 Compliant

## Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

#### ACCESSORIES (ORDER SEPARATELY) XLCC12WH 12" Interconnect cord - White XI CC12BI

XLCC12BL	12″ Interconnect cod - Black	
XLCC24WH	24" Interconnect cord - White	//
XLCC24BL	24″ Interconnect cord - Black	
XLCC36WH	36" Interconnect cord - White	//
XLCC36BL	36″ Interconnect cord - Black	
XLCC48WH	48" Interconnect cord - White	
XLCC48BL	48" Interconnect cord - Black	
XLCC72WH	72" Interconnect cord - White	/
XLCC72BL	72″ Interconnect cord - Black	
XLCP60WH	60″ Cord & Plug - White	1
XLCP60BL	60" Cord & Plug - Black	
XLHBWH	Hardwire Box - White	
XLHBBL	Hardwire Box - Black	
VII. 0. 01		/
XLC-Clips	Clear Cord Clip with Screws (4 pieces)	
LCX-OCC	Occupancy sensor	
		11 1

# **Ordering Information:**

		Lumens						
Size	Black	White	Туре	3000K	LPW	L	W	D
10 in.	ELNU10BK	ELNU10WH	5W	285	57	10″	2-3/4"	1″
14 in.	ELNU14BK	ELNU14WH	8W	508	63	14″	2-3/4"	1″
22 in.	ELNU22BK	ELNU22WH	12W	805	67	22"	2-3/4"	1″
32 in.	ELNU32BK	ELNU32WH	16W	1094	68	32″	2-3/4"	1″
40 in.	ELNU40BK	ELNU40WH	20W	1341	67	40″	2-3/4"	1″

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	













Adjustable Light Bar