



Care and Maintenance on Hardwood and Composite Wood Deck Tiles

Characteristics

Always make certain to clean your deck from crumbs and debris to prevent defects. Although it may seem as if a lot of work, sweeping dust only takes a few minutes and will protect your deck from the elements. The sun is also another factor that can damage your deck.

All timber surfaces will change colour and mellow over time. New tiles will initially vary in shade from items that have been previously purchased.

Clean product with mild soap and water to retain a good level of protection.

Care and clean guidance

Please clean the deck with a soft cloth and a dilute soap solution
Rinse it with water and let it dry thoroughly.

Caution:

Do not use pressure cleaning machines or you will damage the structure of the wood. Obstinate dirt can be removed by applying more pressure when cleaning with soft cloth. Afterwards please polish the surface with a soft cotton cloth.

Then please treat the wood with a type of penetrating oil suitable for Acacia or Eucalyptus wood. Make sure the oil's colour pigmentation matches the colour of the wood. Oil application will help maintain color and avoid damages caused by UV and weather conditions. *(For Hardwood Deck Tiles only)*

For a more intensive treatment, you will need to oil the wood once or twice. Let the tiles get dry for at least 48 hours before using it again. *(For Hardwood Deck Tiles only)*

PLEASE KEEP THESE INSTRUCTIONS FOR FUTURE REFERENCE