

Cole LED Sconce COLS Series

Features

Modern wall sconce with perimeter illumination. Ideal use in hallways, entrances or anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Meets ADA requirements. Fixture can be mounted horizontally or vertically. Fixture mounts to standard junction box (not included).

Construction

Extruded aluminum housing. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black, Gold or Satin Nickel.

Diffuser

White acrylic diffuser.

Electrical

Input 120 VAC 60 Hz. Compatible with residential TRIAC and ELV dimmers.

LED

Integrated LED modules capable of producing: 19W = 1200 source lumens, 1060 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations. ADA Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 year from date of purchase.

Specifications and dimensions subject to change without notice.

| LOCATION | DATE |
|-------------------|--------------|
| PREPARED BY | QUANTITY |
| COMMENTS | FIXTURE TYPE |
| CATALOG NUMBER | |







Ordering Information:

| | | | | Source | Delivered | | | | |
|-----------------|-----------------|-----------------|-----|--------|-----------|-------|-----|----|--------|
| Black | Gold | Satin Nickel | LED | Lumens | Lumens | ССТ | Н | W | D |
| COLS0518L30D1BK | COLS0518L30D1GD | COLS0518L30D1SN | 19W | 1200 | 1060 | 3000K | 18″ | 5″ | 2-1/2" |