# **User's Manual**



## **INSTALLATION INSTRUCTIONS**

## **Installation Manual**





## **INSTALL THE SHOWER**

No.

1

2

3

4

5

6

7

8

9

10

This product has been inspected and debugged by the factory to the best condition. Please do not disassemble and assemble it yourself.



Description

Thermostatic valve

Panel

shelf

Shower hose

Brass hand shower

Shower head

Shower arm

Decoration cover

Accessories

User manual

Qty

1

1

1

1

1

1

1

1

1

1

Before installing the faucet, please be sure to remove sundries and sludge from the water pipe to prevent sundries from blocking the faucet.



#### 2. Installation Steps 2.1 Size for grooving and assembly



20% 6.69"~7.68"

2.11 Main body size(for your reference, check actual size)

ound to sh

head usually 86.61

The shelf is about 47.24" above the ground

2.12 Wall grooving design and size.(for your reference)

Wall surfa

2.95"~3.74" Embedded depth

#### 2.2 Main body built-in steps

ত

1.Exploded view



2.21 Drill the hole in the wall. Beat expansion strip into the hole (there are 2 pieces expansion strip harden and 2 pieces self-tapping screw, how many be used decided by actual situation)



2.23 After connecting the pipeline, remove the upper cover of the embedded box and testthe water.Confirm that there is no leakage, and then cover the upper cover of the embedded box,at last, cover the pipeline and embedded box with cement.



2.22 Put the main body into the wall. fixed with self-tapping screw, please do not harder seal and make sure it is easy for longtime maintenance



2.24 Effect diagram

35.43"~39.37"



2.14 Join different water pipe, the pipe must be connected with hot water on the left and cold water on the right when connecting. After the pipeline is buried, the main body can not be connected until the sediment in the pipeline is drained. (PPR water pipe requirements: water inlet 4 / 6 pipes, water outlet 4 pipes,water pipe self provided)



3. General products

**CLEANING CARE** 

In order to keep the appearance of faucet clean, bright and good performance, please take care of the faucet as follows;

- 1. Rinse with water only and dry with soff cotton cloth;
- 2.Use mild liquid and colorless glass cleaner to remove surface dirt and scale film, or use polish without abrasive effect; 3.Do not use abrasive deterfgent, polish, emery cloth, paper towel or scraper, etc.;
- 4.Do not use acid cleaner, or cleaner and soap with insoluble gran etc.;

5. In the process of use, mud my accumulate in the bubbler and make the water flow show, The bubbler can be unscrewed, rinsed with water, and then installed back in place.



