ASSEMBLY AND INSTALLATION INSTRUCTIONS

CR-VLU002 / CR-VLU003 / CR-VLU004

WARNING: BE SURE TO SHUT OFF POWER AT THE MAIN FUSE OR CIRCUIT BREAKER BOX BEFORE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: 1. Before installing, consult local electrical codes for wiring and grounding requirements. 2. READ AND SAVE THESE INSTRUCTIONS.



- 1. Attach the nipple to the mounting strap, then secure it with a washer and hex nut.
- 2. Attach the mounting strap to the outlet box by using two mounting screws.
- 3. Pull out the outlet wires and house grounding wire from the outlet box. Make wire connections using the wire nuts:
 - ---The black wire from the fixture to the black wire from the power source.
 - ---The white wire from the fixture to the white wire from the power source.
 - ---Attach the fixture grounding wire to the mounting strap with the green grounding screw. Then connect it to the house grounding wire with a wire nut.

Carefully put the wires back into the outlet box.

- 4. Attach the fixture to the mounting strap by inserting the nipple, then secure it with the end cap.
- 5. Attach the glass shades onto the glass holders and secure them with the socket rings.
- 6. Install bulbs (not included). See relamping label at socket area or packaging for maximum allowed wattage.
- 7. Turn on the power at the main fuse or circuit breaker box.

