T4190NLN08



Design By -

Ernesto Gismondi

Collection ===

Outdoor



Colors & Finishes -

| I | White | RAL9002 |
|---|-------|---------|
| | | |

Materials =

- Body in aluminum
- Upper and lower diffusers in silkscreened tempered glass

| Delivered lumens | 407lm |
|------------------------------------|-----------------------------|
| Light output ratio | 31.31lm/W |
| Power consumption | 13W |
| Led type | X10W Array* + X2W Array* |
| CCT (Correlated Color Temperature) | 4000K |
| CRI (Color Rendering Index) | >80 |
| Life expectancy | 50000Hrs |
| Control type | On/Off |
| Input Voltage | 120V |
| Driver | MEAN WELL - 1 x APC-16-700 |
| BUG Rating | B0-U3-G0 |

Features & Accessories =

- Can be installed in both directions depending on desired lighting effect
- Electronic driver integrated
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative

Dimensions ===










4 ^{3/16}" 10.6 cm

Packaging =

1 x 14-11/16" x 14-11/16" x 7-1/8" / 6.33 lbs - 37 cm x 37 cm x 17.8 cm / 2.87 kg

Light distribution =

Direct/Indirect



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane

Luminaire weight -

4.41 lbs / 2 kg

Warranty ==

5 year limited warranty

