

## DORADO - OWC | LED Wall Mount Cylinder

The Dorado 4" LED Wall Mount Cylinder delivers optimal performance in an attractive, round or square contemporary design. Use where ambient illumination is desired, the Dorado uses tempered, clear prismatic glass to create uniform down or up/down light distribution free of hot spots or glare. The fixture features a detachable mounting plate for easy mounting to J-Boxes.

- Die-cast aluminum housing with detachable mounting plate
- Easy to use mounting plate allows for quick mounting to J-Boxes
- Offered in single and up/down configurations
- Operating temperature rating of -4° to 104°F (-20°C to 40°C)



**Applications:** *Ideal for porches, columns, office spaces, restaurants, clubs, walkways and other residential or commercial applications*

### DORADO - OWC Quick Reference Guide

<b>Lm</b> 1390	<b>W</b> 35	<b>Lm/W</b> 40-46	<b>CCT</b>	<b>FINISH</b> Bronze, White
			<div style="display: flex; gap: 10px;"> <div style="background-color: #ff9933; padding: 5px;">3K</div> <div style="background-color: #ffcc00; padding: 5px;">4K</div> <div style="background-color: #0070c0; padding: 5px;">5K</div> </div>	<div style="display: flex; gap: 10px;"> <div style="background-color: #663333; width: 15px; height: 15px;"></div> <div style="background-color: #cccccc; width: 15px; height: 15px;"></div> </div>



\* Only on direct configuration



KNOCKOUTS



1/2" knockout for conduit feed or sensors

DISTRIBUTION



Uniform distribution while maximizing lumen output

### Ordering Information

Ex. OWCR4D1022MV50BZ

Series	Shape	Distribution	Version	Wattage	Voltage	CCTs	Finish
OWC	R4	D (Down)	10 (Version 1)	22 (22W) <sup>1</sup>	MV (120-277)	30 (3000K)	BZ (Bronze)
	S4	U (Up/Down)		33 (33W) <sup>2</sup>		40 (4000K)	WH (White)
				35 (35W) <sup>3</sup>		50 (5000K)	

1) Only available in Down configuration 2) Only available in Up/Down configuration on Square fixture 3) Only available in Up/Down configuration on Round fixture  
See spec sheet for the most up-to-date info