


# PLUTO

3W | 180 lm | 2200K

PLUT-3W-2200K-E26-T-120V

Pluto 3W 2200K E26 Tinted US LED Bulb

tala®



## PHYSICAL


Bulb diameter:	1 3/4 in
Bulb length:	2 7/8 in
Glass shape:	G14
Base:	E26
Materials:	glass and nickel
Glass finish:	Tint
Weight:	0.04 lbs
Max. working temp.:	Max. 40°C
IP rating:	IP54

## ELECTRICAL


Power:	3W
Current:	0.03 A
Voltage:	110-120V~ V
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	60 lm/W
Lifetime:	30000 hrs

## ILLUMINATION

CCT:	2200K
Lumens:	180 lm
Incandescent equiv.:	19W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	75
TM30 - Rg	100
TM30 - Rf	90



IES/LDT photometry files  
and product photography  
available on request



Intertek



## DIMMING

Dimmable 0-100%  
Recommended dimmer: Lutron Diva DVELV-300P  
(For a full list of recommended and compatible  
dimmers see website)

Tala Energy Ltd. 25b Vyner Street,  
London, E2 9DG, United Kingdom

Tala North America, Inc., 2 Research Place,  
Suite 300, Rockville, MD 20850

## WARRANTY

2 years

[talalighting.com](http://talalighting.com) | [hello@tala.co.uk](mailto:hello@tala.co.uk) | +1 (240) 724-8111

## EAN

5061046292014

Specification subject to change without  
notice. Refer to our website for the most  
recent product documentation. Tala  
designs in the EU/UK are protected by  
registered and or unregistered design rights