

Features

- Cross handle style option.
- 7-1/2" (191 mm) gooseneck non-diverter spout with slip-fit connection.

Material

- Brass construction.
- KOHLER finishes resist corrosion and tarnishing.

Installation

Deck-mount

Required Products/Accessories

K-300-K High Flow Bath Valve

- or
 - K-300-KR High Flow Valve w/ Rigid Connections

or K-301-K ¾" High-Flow Bath Valve

Optional Products/Accessories

58598 Deep Rough-in Kit



ADA

Codes/Standards ASME A112.18.1/CSA B125.1 ADA ICC/ANSI A117.1

KOHLER[®] Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

| CP | Polished Chrome | |
|----|-----------------|--|
| 01 | | |

- SN Vibrant® Polished Nickel
- PGD Vibrant® Moderne Polished Gold
- BGD Vibrant® Moderne Brushed Gold
 - G Brushed Chrome
- BN Vibrant® Brushed Nickel
- BV Vibrant® Brushed Bronze
 - BL Matte Black



Purist[®] Bath Faucet Trim K-T14428-3

Purist® **KOHLER**, Faucets **Bath Faucet Trim** K-T14428-3 –7-1/2" (191 mm)– - 2-1/2" (64 mm) 3-1/2" (89 mm) 11-3/8" (289 mm) 7-3/4" Φ (197 mm) Ø 2-1/2" 4-3/4" (64 mm) (121_mm) 1/4" (6 mm) -2-1/8" (54 mm) Max Rim or -1/4" (6 mm) -+ 2-1/8" (54 mm) 1-1/4" (32 mm) Max Finished Deck Max Rough Deck **Deck Mount** Ø 7/8" Ø 1-5/16" (22 mm) (33 mm)

Rim or Deck-Mount Installation Rough + Finished Deck-Mount Installation

3/4" ID

-8" (203 mm) Min-

Technical Information

All product dimensions are nominal.

Notes

Install this product according to the installation instructions.

ADA compliant when installed to the specific requirements of these regulations.

