T417100W08



Design By -

Ernesto Gismondi

Collection =

Outdoor



Colors & Finishes =



Materials =

- Lamp support in painted extruded aluminum
- Base in painted steel
- Lighting unit in die-cast aluminum
- Reflectors in metallic polycarbonate
- UV resistant diffuser in shock resistant polycarbonate

Specifications —

Delivered lumens	504lm
Light output ratio	34.52lm/W
Power consumption	14.6W
Led type	14W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	On/Off
Input Voltage	120V
Driver	MEAN WELL - 1 x APC-16-350
BUG Rating	B0-U2-G0

Features & Accessories =

- Base contains holes for floor installation by means of log bolts and dowels
- Provided with cable and IP67 connector
- Electronic driver integrated
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative

Dimensions =

1 316" - 3 cm | 3 18" - 8 cm | 17 11/16" 45 cm


Packaging =

1 Box

1 x 9-1/8" x 9-1/8" x 27-5/8" / 9.92 lbs - 23 cm x 23 cm x 70 cm / 4.5 kg

Light distribution =

Direct



Luminaire weight —

7.5 lbs / 3.4 kg

Warranty —

5 year limited warranty

Red = Max Cd. Through Vertical plane
Blue = Max Cd. Through Horizontal plane