



Persuade® Comfort Height®

Elongated chair height toilet bowl
K-4326

Features

- Elongated bowl offers added room and comfort.
- Comfort Height® feature offers chair-height seating that makes sitting down and standing up easier for most adults.
- Skirted trapway simplifies cleaning.
- Seat not included.
- Combines with the K-3569 or K-7312 tank to create a complete K-6355 or K-3815 Persuade toilet.
- Combines with the K-19042 tank to create a complete K-75790 Persuade toilet.
- Coordinates with other products in the Persuade collection.
- Standard 12" (305 mm) rough-in only. Cannot be combined with K-5383, or K-5381 for use in 10" or 14" installations.

Installation

- Standard 12" (305 mm) rough-in.
- Patented ReadyLock™ installation system is a simple solution for skirted toilets that saves time, hassle and eliminates the need to drill into the floor for a standard 12" (305 mm) rough-in.

Recommended Products/Accessories

K-3569 Toilet tank, dual-flush
K-7312 Toilet tank, dual-flush
K-23726 Drain treatment

Included Components

Additional Components:
ReadyLock™ installation system



Codes/Standards







ASME A112.19.2/CSA B45.1
ASME A112.19.14
DOE - Energy Policy Act 1992

KOHLER® Toilets and Seats Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
	7	Black Black™



Persuade® Comfort Height®

Elongated chair height toilet bowl

K-4326

No image available.

This product is a component and not intended to be a standalone installation.

Technical Information

All product dimensions are nominal.

Toilet type:	Two-piece, Floor-mount
Waste Outlet:	Floor
Bowl shape:	Elongated
Trap passageway:	2" (51 mm)
Water surface size:	4-1/2" x 5-3/4" (114 mm x 146 mm)
Rough-in:	12" (305 mm)
Seat-mounting holes:	5-1/2" (140 mm)

Notes

Install this product according to the installation instructions.