

LED PENDANT

Ceiling stem mount • Dry location listed



Specifications:

Description:

One-light retro style LED Pendant with prismatic glass. 3000K, 90+ CRI, 1,211 lumens. Dimmable to 10% with ELV type dimmers.

Construction:

- Venetian Bronze (-74) (plated)
- Prismatic glassLED Module is replaceable (part # 93053641)
- Flicker-free dimming to 10% brightness with most ELV type dimmers (See Dimming Notes)
- Title 24 compliant
- Canopy covers a standard 4" hexagonal recessed outlet box
- Mounting strap for outlet box included
- Fifteen feet of wire supplied

Performance:

Number of Modules	1
Input Power	17W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	1211/71.2 (LM-79) per module
CCT	3000K
CRI	90
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cCSAus Dry location listed
	ENERGY STAR® qualified

P5053-7430K9

Images:



Dimensions:

Diameter: 14-5/8"
Height: 6-5/8"
Overall ht. w/stem: 72-5/8"

Catalog number:

Base	Finish	Color Temp	CRI
P5053	74 - Venetian Bronze	30K - 3000K	9 - 90 CRI

LED PENDANT

Ceiling stem mount • Dry location listed



P5053-7430K9

Dimming Notes:

P5053 is designed to be compatible with many Electronic Low Voltage (ELV-Reverse Phase) controls.

The following is a partial list of known compatible dimmer controls:

Electronic Low Voltage ELV Reverse Phase Controls

Lutron	Diva Series	(Part Number DVELV-300P)
Lutron	Nova T Series	(Part Number NTELV-300)
Lutron	Vierti Series	(Part Number VTELV-600)
Lutron		(Part Number MAELV-600)
Lutron		(Part Number SPELV-600)
Leviton		(Part Number AWRMG-EAW)
Leviton		(Part Number 6615-P)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.