


TUBE ARCHITECTURAL DS-PD05

LED Pendant Mounts

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

FEATURES

- High performance exterior rated LED pendant
- Includes 45° swivel canopy and two field cuttable 24" rods
- Rods extendable up to 96" using DS-PDX24 accessory
- Solid aluminum construction
- 39° visual cutoff angle for glare control
- 5 year warranty

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 5% (120V only)
0-10V: 100% - 0% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB
Rated life of 60,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, ETL & cETL wet location listed
- Operating Temperature:** -40°F to 122°F (-40°C to 50°C)

ORDERING NUMBER

Model	Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (Lm/W)	Light Distribution	Finish	
DS-PD05	5"	27W	S927	2700K	90	1680	8526	62	18°	BK Black WT White BZ Bronze GH Graphite
			S27	2700K	85	1800	9151	67		
			S930	3000K	90	1700	8639	63		
			S30	3000K	85	1995	10126	74		
			S35	3500K	85	2190	11118	81		
			S40	4000K	85	2260	11483	84		
			N927	2700K	90	1730	5513	64	25°	
			N27	2700K	85	1855	5918	69		
			N930	3000K	90	1750	5587	65		
			N30	3000K	85	2055	6548	76		
			N35	3500K	85	2255	7190	84		
			N40	4000K	85	2330	7426	86		
			F927	2700K	90	1725	4246	64	33°	
			F27	2700K	85	1850	4557	69		
			F930	3000K	90	1745	4302	65		
			F30	3000K	85	2045	5043	73		
			F35	3500K	85	2245	5537	83		
			F40	4000K	85	2320	5719	86		

DS-PD05-_____ - _____

Example: DS-PD05-S930-WT

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760



TUBE ARCHITECTURAL DS-PD05

LED Pendant Mounts

WAC LIGHTING

Responsible Lighting®

MOUNTING ACCESSORIES

	<i>Extension Rod</i>	DS-PDX24	<i>One 24" extension rod for DS-PDSK Can be field cut</i>	Finish	
				BK <i>Black</i>	
				WT <i>White</i>	
				BZ <i>Bronze</i>	
				GH <i>Graphite</i>	

Example: **DS-PDX24-WT**

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122


Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

TUBE ARCHITECTURAL DS-PD06

LED Pendant Mounts

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

FEATURES

- High performance exterior rated LED pendant
- Includes 45° swivel canopy and two field cuttable 24" rods
- Rods extendable up to 96" using DS-PDX24 accessory
- Solid aluminum construction
- 38° visual cutoff angle for glare control
- 5 year warranty

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 5% (120V only)
0-10V: 100% - 0% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB
Rated life of 70,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, ETL & cETL wet location listed
- Operating Temperature:** -40°F to 122°F (-40°C to 50°C)

ORDERING NUMBER

Model	Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (Lm/W)	Light Distribution	Finish	
DS-PD06	6"	36W	S927	2700K	90	1875	8911	51	19°	BK Black WT White BZ Bronze GH Graphite
			S27	2700K	85	2400	11392	65		
			S930	3000K	90	2000	9500	54		
			S30	3000K	85	2170	10317	59		
			S35	3500K	85	2500	11884	68		
			S40	4000K	85	2450	11639	66		
			N927	2700K	90	1830	4642	49	30°	
			N27	2700K	85	2340	5935	63		
			N930	3000K	90	1950	4949	53		
			N30	3000K	85	2120	5374	57		
			N35	3500K	85	2440	6191	66		
			N40	4000K	85	2390	6063	65		
			F927	2700K	90	1840	3310	50	40°	
			F27	2700K	85	2355	4231	64		
			F930	3000K	90	1965	3528	53		
			F30	3000K	85	2130	3832	58		
			F35	3500K	85	2455	4414	66		
			F40	4000K	85	2405	4323	65		

DS-PD06-_____-____-

Example: DS-PD06-S930-WT

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760



TUBE ARCHITECTURAL DS-PD05

LED Pendant Mounts

WAC LIGHTING

Responsible Lighting®

MOUNTING ACCESSORIES

	<i>Extension Rod</i>	DS-PDX24	<i>One 24" extension rod for DS-PDSK Can be field cut</i>	Finish	
				BK <i>Black</i>	
				WT <i>White</i>	
				BZ <i>Bronze</i>	
				GH <i>Graphite</i>	

Example: **DS-PDX24-WT**

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122


Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

TUBE ARCHITECTURAL DS-PD08

LED Pendant Mounts

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options

FEATURES

- High performance exterior rated LED pendant
- Includes 45° swivel canopy and two field cuttable 24" rods
- Rods extendable up to 96" using DS-PDX24 accessory
- Solid aluminum construction
- 43° visual cutoff angle for glare control
- 5 year warranty

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
Dimming: 0-10V: 100% - 20% (120-277V)
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 80,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite
Standards: IP65 rated, ETL & cETL wet location listed
Operating Temperature: -40°F to 122°F (-40°C to 50°C)

ORDERING NUMBER

Model	Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (Lm/W)	Light Distribution	Finish	
DS-PD08	8"	54W	S927	2700K	90	2860	20455	53	14°	BK Black WT White BZ Bronze GH Graphite
			S27	2700K	85	3365	24065	62		
			S930	3000K	90	3230	21796	60		
			S30	3000K	85	3670	24490	68		
			S35	3500K	85	4015	28660	74		
			S40	4000K	85	3650	15121	68		
			N927	2700K	90	2890	6851	54	28°	
			N27	2700K	85	3400	8060	63		
			N930	3000K	90	3318	7907	61		
			N30	3000K	85	3770	8885	70		
			N35	3500K	85	4005	9390	74		
			N40	4000K	85	3675	12052	68		
			F927	2700K	90	2886	4633	53	40°	
			F27	2700K	85	3395	5450	63		
			F930	3000K	90	3322	5407	62		
			F30	3000K	85	3775	6075	70		
			F35	3500K	85	4005	6490	74		
			F40	4000K	85	3725	5443	69		

DS-PD08-_____-____

Example: DS-PD08-S930-WT

wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760



TUBE ARCHITECTURAL DS-PD05

LED Pendant Mounts

WAC LIGHTING

Responsible Lighting®

MOUNTING ACCESSORIES

	<i>Extension Rod</i>	DS-PDX24	<i>One 24" extension rod for DS-PDSK Can be field cut</i>	Finish	
				BK <i>Black</i>	
				WT <i>White</i>	
				BZ <i>Bronze</i>	
				GH <i>Graphite</i>	

Example: **DS-PDX24-WT**

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760