

Features

- 0.5 gal/min (1.9 l/min) flow rate.
- Factory set 30 second max. continual run cycle.
- Vandal-resistant aerator.
- 24" (610 mm) flexible supply hoses for easy installation.
- 6-3/16" (157 mm) spout reach.
- Less temperature mixer.
- Less drain.

Material

Brass Construction.

Technology

- Includes two AAA batteries.
- Electronic Insight[™] Sensor Technology for accurate and consistent activation.

Installation

- Single-hole mounting.
- Above-counter battery and valve for easy installation and maintenance.

Optional Products/Accessories

1160593 .35 gpm Aerator, Small 1139286 Small Aerated 1.0 gpm (3.8 l/min) 1139287 Small Laminar 1.0 gpm (3.8 l/min) 1053576 Small Aerated 1.5 gpm (5.7 l/min) 1053532 Small Laminar 1.5 gpm (5.7 l/min) 78783 Sealing Washer 1075440 Small Spray 0.5 gpm (1.9 l/min)



ADA CSA B651 OBC

Codes/Standards

ASME A112.18.1/CSA B125.1 NSF/ANSI 372 All applicable US Federal and State material regulations DOE - Energy Policy Act 1992 ADA ICC/ANSI A117.1 CSA B651 OBC

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description




CP Polished Chrome

VS Vibrant® Stainless



Deck Mount Faucet K-13473

KOHLER. Faucets



Technical Information

All product dimensions are nominal.

| Power source: | Battery - DC, included |
|---------------|-------------------------|
| Faucet: | |
| Flow rate: | 0.5 gal/min (1.9 l/min) |
| Pressure: | 60 psi (4.1 bar) |
| Valve body: | Machined-brass |

Notes

Install this product according to the installation guide.

A 1-1/4" (32 mm) minimum to 1-1/2" (38 mm) maximum diameter mounting hole is required. The minimum distance between the back of the faucet spout and the wall must be 1-3/4" (44 mm). This will allow proper clearance for setscrew access.

The maximum distance between the bathroom sink basin edge to the base of the faucet spout must be 1-3/4" (44 mm).

The maximum height of the lip basin should be 3/4" (19 mm).

Product includes rosebud spray aerator. Other aerator styles are available.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

